

Diesel Powered Generating Sets C70 D6



Standard Genset Features

Cummins water cooled Diesel engine,
Oil and fuel filter fitted, water separator,
Lube-oil drain valve fitted
Electric starter & Charge alternator 12 v D.C.
Mechanical governor
Normal duty air filter
Single bearing alternator, class H/H
Standard voltage 480/277 volts 60 Hz
Exciter/Voltage reg - Torque Match as std
PCC1301 (PCC2100 as Option)
3 pole C/B
Bolted steel base frame with A/V mounting,
Fork lift pockets in baseframe
Single skin plastic fuel tank
Tank capacity of min 8 hours operation at
70% standby load
Loose 9 dB(A) silencer
Set mounted starting batteries
Engine & Alternator Munsell Jade Green
Chassis, Controller box and radiator black
Packing under shrunk plastic film
Operation & Maintenance manual
Standard set of labels

Generator Set Performance

Voltage Regulation
Maintains voltage output to within $\pm 1.0\%$.
At any power factor between 0.8 and 1.0
At any variations from No load to Full load.
At any variations from Cold to Hot.
At speed droop variations up to 4.5%.
Frequency Regulation
Isochronous under varying loads from no
load to 100% full load when electronic
governor is fitted.
Random Frequency Variation
Will not exceed $\pm 0.25\%$ of its mean value for
constant loads – no load to full load.
Waveform
Total harmonic distortion open circuit voltage
waveform in the order of 1.8%. Three-phase
balanced load in the order of 5.0%.
Telephone Influence Factor (TIF)
TIF better than 50.
THF to BS 4999 Part 40 better than 2%.
Alternator Temperature Rise
Class H insulation.
Radio Interference
In compliance with BS 800 and VDE levels
G and N.

Generator Set Options

Mechanical Options
Compliance - CE Certification (Guarding)
Fuel options
Fuel Tank deletion
Exhaust Options
Exhaust Silencer - Industrial (9 dB), In-Line
Exhaust Bellows
Exhaust Silencer - Residential (25 dB), In-Line
Installation Kit - Industrial Silencer
Warranty
Warranty - 5 Year Extended Standby Appl
Warranty - 2 Year Extended Prime Appl
Voltage Connections
277/480V
254/440V
240/416V
220/380V
139/240V
127/220V
120/208V

Engine Specification

4BTA3.9G2
In-line direct injection
4-cylinder diesel engine.
Type
Water cooled, four cycle, turbocharged
and after cooled.
Construction
Two valves per cylinder, forged steel
crankshaft and connecting rods, cast iron
block.
Starting
12 volt negative earth. Battery charging
alternator 37 amp on engine. Cranking
current 625 amps at 0°C.
Fuel System
12 volt fail safe actuator. Spin-on paper
element fuel filters with Stanadyne fuel
pump injection system with integral
mechanical governor. Dual flexible fuel lines
and connectors. Standard fuel water
separator.
Filters
Air cleaner with dry element and restriction
indicator. Spin-on full flow lube oil filter.
Cooling
50°C radiator as std
Stone guard. Oil cooler. Drain Tap

Alternator Specification

Type
Brushless single bearing, revolving field,
pole, drip proof, screen protected.
Class H Insulation.
IC 01 cooling system.
Fully interconnected damper winding.
AC exciter and rotating rectifier unit.
Epoxy coated stator winding.
Rotor and exciter impregnated with tropical
grade insulating oil and acid resisting
polyester resin. Dynamically balanced rotor
BS 5625 grade 2.5.
Sealed for life bearings.
Layer wound mechanically wedged rotor.
Exciter
Triple dipped in moisture, oil and acid
resisting polyester varnish and coated with
anti-tracking varnish.
Output windings with 2/3 pitch for improved
harmonics and paralleling ability.
Close coupled engine/alternator for perfect
alignment.

Miscellaneous Options

Coolant heater -240V
Battery Charger 240V,5A
AUTO START - AMF Module (Loose)
Packing - Export Box
4 POLE MCCB

Compliance Standards

To BS4999/5000 pt 99,
VDE 0530, UTE5100,
NEMA MG1-22, CEMA,
IEC 34, CSA A22.2,
AS1359, BSS 5514,
ISO 3046 and ISO 8528

Model name	kVA		kWe	
	ESP	PRP	ESP	PRP
C70 D6	87.5	81.3	70.0	65.0

TECHNICAL DATA

Model	C70 D6	Speed	1800 rpm
Set output	380 480 V 60 Hz	Alternator voltage regulation	±1.0%
Prime Rating	65 kW/81 kVA	Alternator insulation class	H
Standby Rating	70 kW/88 kVA	Fuel consumption (Prime)	18 l/hr
Engine Make	Cummins	Fuel consumption (Standby)	20 l/hr
Engine Model	4BTA3.9G2	Lubrication system oil capacity	10.9 Litres
Cylinders	Four	Base fuel tank capacity – open set	112 Litres
Engine build	In-line	Coolant capacity	17.9 Litres
Standard Governor/Class	Mechanical	Exhaust temp – prime	461 °C
Aspiration and cooling	Turbocharged And Jacket Water Aftercooled	Exhaust gas flow – prime	225 l/s
Bore and stroke	102 mm x 120 mm	Exhaust gas back pressure max	76 mm Hg
Compression Ratio	16.5:1	Air flow – radiator*	1.71 m ³ /s
Cubic capacity	3.92 Litres	Air intake – engine (Prime)	97 Litre/s
Starting/Min °C	Unaided/-12°C	Minimum air opening to room	0.7 sq m
Battery capacity	100 A/hr	Minimum discharge opening	0.45 sq m
Gross Engine output – Prime	77kW/m	Pusher fan head (duct allowance)*	13 mm Wg
Gross Engine output – Standby	84kW/m	Heat radiated by eng (Prime)	14.2 kW/m

PRIME POWER (PRP)

Prime power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO8528-1.

A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation, in accordance with ISO 3046-1.

STANDBY POWER RATING (ESP)

The Standby Power Rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

In installations served by unreliable utility sources (where outages last longer or occur more frequently), where operation is likely to exceed 200 hours per year, the prime power rating should be applied.


The Standby Power rating is only applicable for emergency and standby applications where the generator set serves as the back up to the normal utility source.

All ratings are based on the following reference conditions:

- Ambient temperature – 27°C

- Altitude above sea level – 150 metres

- Relative humidity – 60%



Dimensions and Weights

Model	Engine	Length (mm)	Width (mm)	Height (mm)	Set weight wet (Kg)	Set weight dry (Kg)	Enclosed Weight Wet (Kg)
C70 D6	4BTA3.9-G2	2686	1300	1547	1900	1840	3196

Specifications may change without notice

Cummins Power Generation Limited

Manston Park, Columbus Avenue

Manston, Ramsgate

Kent CT12 5BF, UK

Telephone: +44 (0)1843 255000

Fax: +44 (0)1843 255902

Email: cpg.uk@cummins.com

www.cumminspower.com

www.cummins.com

See your distributor for more information.

